

The safe and easy way to realign your doors

HINGE

Tweaker™

Hinge Tweaker
2002 West 16th Street
Erie, PA 16505

Phone 1-866-455-4799
Fax 814-454-0275
sales@hinetweaker.com
www.hinetweaker.com

A division of Builders' Hardware



We thank you for your interest in our commercial grade Hinge Tweaker alignment tools.

Per your request, attached you will find the following:

- Hinge Tweaker Tools
- Directions
- Order Form

Leverage



If you have any specific questions or if you would like to place an order over the phone please give us a call during normal business hours. For your convenience, we have also enclosed an order form, which can be faxed directly to our dedicated team of sales professionals. Once again thank you for your interest in our commercial grade Hinge Tweaker alignment tool.

Standard Weight Hinge Tweaker



Features and Benefits

- Designed to fit standard weight .134 gauge hinges
- Powder coat finish
- Ergonomic grip
- High-visibility red is easy to locate quickly
- Welded - one-piece steel construction for increased strength and durability

\$69.95

Standard Weight

- No more sticking
- No more rubbing
- No more jamming
- No more scratched paint

Blue Streak Heavy Weight Hinge Tweaker



Features and Benefits

- Designed to fit standard weight .180 gauge hinges
- Powder coat finish
- Ergonomic grip
- High-visibility blue is easy to locate quickly
- Welded - one-piece steel construction for increased strength and durability

\$79.95

Heavy Weight

“Blue Streak” Hinge Tweaker

- Bigger Barrel
- 6” Longer in Length
- The Leverage You Need

What is the purpose of a Hinge Tweaker?

The Hinge Tweakers are therapy for your doors. To be more precise, the Standard Weight Hinge Tweaker is designed to rebend standard weight .134 gauge hinges. The Heavy Weight Hinge Tweaker is designed to rebend heavy weight .180 gauge hinges. Both the Standard Weight and Heavy Weight Hinge Tweaker will help you enable the door to operate correctly. In the door and hardware industry we would effectively call this rebending technique, "closing the swedging of a hinge" or "closing the gap".

The Hinge Tweakers when used correctly can be a time and labor saver. Utilize the Hinge Tweaker and give a lift to your sagging doors. The Hinge Tweakers can be used to correct minor improper door to frame clearances.

Which door hinge do I place the Hinge Tweaker on?

Most frequent adjustments will be completed on the top door hinge. Why only the top hinge you ask? Simply stated, the top door hinge realizes the greatest stress because it carries the majority of the door weight. Therefore, in standard door operating conditions the top hinge will bend and spread apart more than other hinges on the same door. The second most frequent hinge adjustment will be the middle hinge. On rare occasion you might also find a need to rebend the bottom hinge.

How do I use the Hinge Tweaker?

1. Leave the door hanging and swinging. There is no need to remove the door.
2. Close the door
3. Slide the Hinge Tweaker over the hinge knuckles of the bent hinge while the door is in closed position.
4. Bend the hinge slightly by pushing the Hinge Tweaker away from the door knob/lever side of the door.
5. After bending the hinge slightly, remove the Hinge Tweaker, then check the swing of the door by opening and closing the door as normal. Make your hinge bending adjustments just a little at a time to avoid over bending and over compensating the hinge and frame.
6. Repeat the hinge bending process as necessary to get the desired results of having the door close properly.

